FL FURNACE

25 liters

Technical Datasheet



Design and production of custom-made furnaces

We specialize in the design and manufacturing of industrial furnaces used in processes that require precise temperature control.

www.samothermal.com





Technical datasheet FL FURNACE

25 liters

APPLICATIONS

- Non-ferrous metal casting
- Soil analysis
- Chemical laboratories
- Mining
- 3D jewelry
- Dental mechanics
- Glass fuse
- Ceramics

FEATURES:

Electronic programmer with storage capacity for 4 programs of 6 segments each, featuring ramp hold fire programs. It also includes pre-loaded programs for direct cone firing in ceramics. It has a delay and automatic program end alarm.

Internal Chamber dimensions:

Height: 30 cm Width: 30 cm Depth: 30 cm

External dimensions:

Height: 61 cm Width: 46 cm Depth: 60 cm

Volume: 25 liters

Internal Chamber Material:

High alumina refractory bricks

Continuous Temperature: 1250°C

Current: 26A Tension: 220V Power: 5720 Watts

Number of Phases: 2

Thermocouple:

Type K with ceramic coating.

Heating Elements:

Spiral wire of Kanthal alloy

Temperature Measurement Variation: ± 1°C

Switch: It has a switch for turning the oven on and off.





Warranty: 1 year against manufacturing defects. Delivery time: 2 to 3 weeks.







