


CS KILN 10-27 C7

Technical Datasheet



Design and production of custom-made furnaces

We specialize in the design and manufacturing of industrial furnaces used in processes that require precise temperature control.

www.samothermal.com



hornos
samo thermal



samothermal

Technical datasheet

CS KILN 10-27 C7

APPLICATIONS

- Glass fusion
- Ceramics

FEATURES:

Electronic programmer with the capacity to store 4 programs of 6 segments each, featuring temperature ramp speed control and holding time. It includes pre-loaded programs for direct cone firing for ceramics, delay (ignition delay), and automatic end-of-program alarm.

Internal Chamber dimensions:

Height: 71 cm
Diameter: 53 cm

External dimensions:

Height: 94 cm
Diameter: 74 cm

Internal Chamber Material:

High alumina refractory bricks

Maximum Temperature: 1250 °C (cono 7)

Current: 50 A

Tension: 220V

Power: 11000 Watts

Number of Phases: 1

Thermocouple:

Type K with ceramic coating.

Heating Elements:

Spiral wire of Kanthal alloy

Temperature Measurement

Variation: $\pm 1^{\circ}\text{C}$



Foto referencial



Foto referencial

Warranty: 1 year against manufacturing defects.

Delivery time: 2 to 3 weeks.

